



# Top Reach Solutions

Access Above Altitude

**TAMILNADU | KARNATAKA | ANDHRA**



**OUR FOCUS**

**Aluminium Scaffolding Towers  
Sales | Rental**



Call us @ + 91 - 9962453727

Mail us @ [topreachsolutions@gmail.com](mailto:topreachsolutions@gmail.com)

# Available Working Heights -from 2 Meters to 16 Meters



## FOR YOUR SAFETY

- ✓ The Locking system in our Castors creates a safe suitable scaffold by preventing the roll & swivel of caster.
- ✓ Advance safety clamps are provided for RUNG FRAMES which keeps the scaffolding structure safer.
- ✓ Colour coded horizontal and diagonal braces for easy erection and identification fitted with self-priming triggers that automatically lock when attached to the tower.
- ✓ Extra stable Guard Rails - for even greater safety and stability.
- ✓ Advanced Stabilizers to increase the effective base dimensions and improve the STABILITY of the tower.
- ✓ Multi rung frames which increases the flexibility of working heights.



Call us @ + 91 - 9962453727

Mail us @ [topreachsolutions@gmail.com](mailto:topreachsolutions@gmail.com)

# ALUMINIUM SCAFFOLDING TOWERS

The aluminium scaffolding towers are greatly used because of their durability, lightweight, uniform structure, withstanding harsh weather conditions, dimensional accuracy, high flexibility and resistance against cracks or corrosion. These towers are widely used for construction of tall buildings, repair works, roads and dams, painting of large apartments and many more. Due to its lightweight nature, these scaffoldings can be moved easily from one place to another.

## OUR SCAFFOLDING TOWER TYPES

- ✓ STAIRWAY TYPE SCAFFOLDING TOWER (ZIG ZAG TYPE)
- ✓ STAIRWAY TYPE SCAFFOLDING TOWER (LANDING PLATFORM TYPE)
- ✓ BRIDGE TYPE SCAFFOLDING TOWER

## SCAFFOLDING TOWER – TECHNICAL SPEC

DESCRIPTION	DIMENSION
SCAFFOLDING LENGTH	2.1 METER
SCAFFOLDING WIDTH	1.5 METER
SCAFFOLDING HEIGHT	FROM 2 METER TO 20 METER
MAXIMUM PLATFORM LOAD	250 KG
PIPE THICKNESS	2 MM
PIPE DIAMETER	50 MM
ALUMINIUM TYPE	6005 T6 TYPE ALLOY / TEMPER

## APPLICATIONS

- ✓ Electronic Industries
- ✓ Automobile Industries
- ✓ Aviation Industries
- ✓ Chemical Treatment Plants
- ✓ Heavy Engineering Industries
- ✓ Steel Industries

## OUR QUALITY

- ✓ All Our Scaffolding Towers Are designed based on The British Standard "BS EN 1004:2004"
- ✓ We use TIG Welding Process for our scaffolding towers which gives very high-quality Weld finish and Provides precise control of welding variable heat via amperage controls also Leave no slag or splatter.
- ✓ Our scaffolding Platforms are made by ISI certified BWR Grade Double Pressed Plywood's which gives superior strength, toughness and durability.
- ✓ Aluminium pipes used by us for the scaffolding are designed, inspected, tested and certified by our supplier based on the standard BS EN 755-2:2008 with a test certificate.

## REACH US

### **HEAD OFFICE :**

No.2/743, Annai Velankanni Nagar Phase-2, Mugalivakkam, Chennai - 600125.

### **CHENNAI BRANCH OFFICE :**

Multi Nagar Main Road, Multi Industrial Estate, Gerugambakkam, Chennai - 600125.

### **STOCK YARD :**

Utthukattu Village, Walajabad, Kancheepuram, TamilNadu - 631605.

### **OTHER BRANCHES :**

Bangaluru, Tada, Hyderabad, Pune, Ahmedabad

Call us @ +91. 9962453727 | E-mail : [topreachsolutions@gmail.com](mailto:topreachsolutions@gmail.com) | [www.topreach.in](http://www.topreach.in)